RRussound_®

New Product Release **ComPoint[™] Intercom System** The music lovers' intercom solution

The first of its kind, Russound's ComPoint Intercom System integrates with multiroom audio systems to provide room-toroom and whole-house communication. Through built-in speakers and attractive keypads, enjoy the benefits of multiroom audio and the convenience of intercom communications without sacrificing sound quality or ease of use.

The days of large intercom boxes mounted on the wall in every room are over. Instead, keypads the size of a light switch, and just as easy to use, offer elegant solutions. Mounted in single-gang workboxes, the basic and advanced keypads, plus the door station offer attractive options for residential intercoms. Simply press the talk or call button to send a page, or select a room first for room-to-room contact. When replying to the intercom, take advantage of the hands-free reply feature.

Among ComPoint's other unique features are the Do Not Disturb mode for room privacy and Listen Mode for listening to one room from any other.

For additional convenience, Russound offers an optional Door Strike Release trigger that integrates with most third party release modules sending a signal to unlock the door.

From outside the home to each room within, ComPoint's performance and exceptional design make it an elegant addition to any multiroom audio system.

Available in kits to fit a variety of applications, each component is made with quality materials. Whether used with a multiroom audio system or as a stand-alone intercom solution*, ComPoint is a sound choice for home communications.

*Built-in or surface mount speakers are required in each room.



ISK2 Advanced Keypad

Benefits

Convenient whole house paging and room-to-room intercom provide valuable communication

Versatile seamless integration with any distributed audio system for easy add-on applications

Full-featured Do Not Disturb, Listen Mode, and hands-free reply

Expandable ComPoint supports up to 36 rooms* for larger homes

Customizable choose from seven doorbell chimes, 65 digital room names* and various finish color options for inside and outside the home

*With ISK2 Keypads only



Specifications

ISH1 Hub

Keypad ports:	(6) 8-pole modular RJ-45
Door station ports:	(2) 8-pole modular RJ-45
Link ports:	(2) 8-pole modular RJ-45
Update port:	4-pole port for Programming Cable, Russound part #2500-521065
Switches:	4-switch DIP for hub ID setting
	8-switch DIP for 2 doorbell settings
	Potentiometer for doorbell volume
Doorbell options:	7 selectable chime patterns plus no chime
Power requirement:	15 VDC 5.5 A (power adapter included)
Mounting method:	Surface or structured wiring panel
Dimensions:	6.438" W x 5.125" H x 1.813" D (16.4 x 13.0 x 4.6 cm)

ISDR1 Door Strike Release Module

Relay contact rating: 5 A @ 12 VDC Mounting method: Surface

CAT-5 connectors: (2) 110 punch-down blocks Strike release relay: 1-pole double-throw (NC/NO) Relay connector: Removable 3-pole screw terminal Relay wire size: Up to 14 AWG (1.63 mm) Dimensions: 3" W x 1.875" H x 1" D (7.6 x 4.8 x 2.5 cm)

ISK3 Door Station

User control:	Call key with amber backlight
Audio input:	Built-in microphone with automatic gain control
Amplifier:	Monaural (for system functions only)
Volume control:	Installer-adjustable potentiometer
Audio output:	Built-in speaker
Cover plate:	Weatherproof plated die-cast zinc
CAT-5 connector:	110 punch-down block
Doorbell connector:	2-pole screw terminal
Doorbell wire size:	Up to 18 AWG (1.024 mm)
Doorbell contact:	1 A @ 12 VDC
Power consumption:	15 VDC 220 mA maximum
Available finishes:	Polished brass, antique brass, brushed chrome
Overall dimensions:	3" W x 5.125" H x 3.25" D (7.6 x 13.0 x 8.3 cm)
Dimensions in wall box:	2" W x 2.875" H x 2.75" D (5.1 x 7.3 x 7.0 cm)
Wall box:	Single gang, 22 cu in. (360 cm ³) minimum volume

ISK1 Basic and ISK2 Advanced Keypads

Key backlighting:	Installer-selectable amber or green, with red
	function indication
Audio input:	Built-in microphone with auto gain control
Min. load impedance:	6 ohms per channel
Speaker relay rating:	50 watts RMS continuous
Speaker connectors:	8-pole screw terminal
Speaker wire size:	Up to 14 AWG (1.63 mm)
CAT-5 connector:	110 punch-down block
Keypad style:	Single-gang Decora®
Available colors:	White, almond, bone, brown, black
Dimensions:	ISK1: 1.875" W x 4.188" H x 2.5" D (4.8 x 10.6 x 6.4 cm)
	ISK2: 1.875" W x 4.188" H x 2.63" D (4.8 x 10.6 x 6.7 cm)

System

ubs)
е
m)
•

Supports 6 zones and 2 door stations 7 selectable chime options Chime level adjustment • Fits most structured wiring cabinets Up to 6 ISH1 hubs can be linked for 36 zones ISH1 · Electronic door strike release trigger module Enables remote entry feature • 5A relay contact closure iciantanta i In-line wiring with ISK3 door station ISDR1 • Low cost option ComPoint door station Single gang electrical box mounting Weather proof design Hands-free reply Available in polished brass, ISK3 antique brass and brushed chrome 0 0 0 · 6 zone Basic paging keypad Talk Intuitive and simple to use DI • A Cost effective 02 00 💌 Amber/ green selectable illumination · Available in white, almond, ivory, ISK1 brown and black Advanced paging keypad LCD panel for ease of use Talk • 65 assignable room names • • Amber/green selectable illumination Available in white, almond, ivory, brown and black ISK2 · For systems up to 36 zones Shc SP-M6TT H.-0 - CAT5 cable === 16/4 speaker wire UNO-S1 R

CAM6.6X

Since 1967, innovation, quality and reliability have been the core of the Russound product tradition. Today, Russound offers everything for enjoying multiroom audio-video in your home. All audio-video distributed solutions are built to high standards and designed with the unique consideration of making products that are easy to live with and enjoy.

Russound

www.russound.com

603.659.5170

5 Forbes Road Newmarket, New Hampshire 03857 USA

©2005 Russound. All rights reserved. All trademarks are the property of their respective owners. Specifications are subject to change without notice. Russound is not responsible for typographical errors or omissions. LR2300-0001